



ALL-PURPOSE

ANTI-SEIZE



FEATURES

- Prevents seizure up to 1800°F (982°C)
- Lead free and moly fortified
- Protects against seizure, heat-freeze, galling, rust and corrosion on large threaded connections
- Lowers friction; reduces wrench torque
- Reduces maintenance costs
- Not affected by contraction, expansion or vibration
- Will not run, drip or settle out
- Steel blue color

Conforms to: MIL-PRF-907E

PACKAGES

Net Fill

- 1/2 lb. (227 grams) paste
- 1 lb. (454 grams) paste

Part No.

- 04108
- 04110

APPLICATIONS

- Fittings
- Flange Faces
- Gaskets
- Guides
- Keys
- Keyways
- Slides
- Tubular Threads

PROPERTIES

Color/Appearance:
Blue/Gray Smooth Paste

Dropping Point (ASTM D-566):
450°F (232°C)

Flash Point (ASTM D-92):
> 430°F (221°C)

Oil Separation, Wt. % Loss
@ 212°F (100°C):
<5.0

Penetration @ 77°F ASTM D-217:
285-315

Salt Fog Resistance (ASTM B-117)
20%NaCl @ 100°F (38°C)
Hrs. Free of Corrosion:
200 +

Shell 4-Ball (ASTM D-2596)
Weld Point kgf:
500

Specific Gravity (Water = 1):
1.0-1.2 @ 68°F (20°C)

Coefficient of Friction:
0.08



MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE :WWW.LPSLABS.COM

LPS Laboratories • An Illinois Tool Works Company

P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: www.lpslabs.com

©2010 LPS Laboratories • LPS® is a registered trademark of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2111 • Rev. 3/2010