



DRY FILM PTFE

LUBRICANT



FEATURES

- Provides excellent lubrication
- Ideal for releasing molded parts
- Excellent for high temperature applications up to 500°F (260°C)
- Dry, thin film will not attract dust or dirt
- Does not contain silicone or chlorinated solvents
- Safe on most surfaces

Qualified to: Learjet M3735-01-98-0042

PACKAGE

Net Content

12 wt.oz. /340 g / 418 ml aerosol

Part No.

02616

APPLICATIONS

- Chutes & Slides
- Conveyor Belts
- Injection Molding
- Locks & Catches
- Metal Extrusions
- Silicone Rubber
- Tanks & Bins
- Thermoplastics
- Thermosets
- Window Guides



PROPERTIES

Appearance/Physical State:

White (when dry)

Evaporation Rate:

>1 (Butyl Acetate=1)

HMIS:

1, 3, 0

Specific Gravity (water=1):

0.64 – 0.66 @ 20°C

Vapor Pressure:

630 kPa (25°C)

Viscosity:

<2 centistokes @ 25°C

VOC Content:

57%

MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE : WWW.LPSLABS.COM

LPS Laboratories • An Illinois Tool Works Company

P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: www.lpslabs.com

©2009 LPS Laboratories • LPS®, PT® and PF® are registered trademarks of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2163 • Rev. 5/2010