



ELECTRO

CONTACT CLEANER

VOC COMPLIANT



FEATURES

- Non-flammable
- No ozone depletion potential
- Fast evaporating, no residue
- Quick penetration
- Ideal for electrical/electronic fine parts
- Removes light greases, oils, dirt and organic soils
- Non-conductive
- Safe on plastics
- Does not contain HCFCs
- Conforms to CARB (California Air Resources Board), OTC (Ozone Transport Commission) and LADCO (Lake Michigan Air Directors Consortium)

PACKAGE

Net Content

14 wt.oz. /397 g/ 301 ml aerosol

Part No.

00416

APPLICATIONS

- Calculators
- Computers
- Digital Equipment
- Electronic Ignitions
- Navigation Equipment
- Printed Circuits
- Radars
- Radios
- Switches and Relays



PROPERTIES

Auto Ignition Temperature:

>482°F (250°C)

Boiling Point (°C):

118°F (48°C) @ 1 atm

Color:

Colorless

Dielectric Strength Breakdown

Voltage (ASTM D877):

22 kV

Flash Point (°C) TCC:

None.

Specific Gravity (Water=1):

1.38 – 1.40 @ 77°F (25°C)

Solubility Description:

<5% by weight.

Vapor Density (air=1):

>1

Vapor Pressure:

60 psi @ 77°F (25°C)

Viscosity:

<3 cSt @ 77°F (25°C)

VOC content

62.5% , 840 g/L, 7.3 lb/gal

per CARB

Volatiles:

100%

MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE : WWW.LPSLABS.COM

LPS Laboratories • An Illinois Tool Works Company

P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: www.lpslabs.com

©2010 LPS Laboratories • LPS® is a registered trademark of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2107 • Rev. 5/2010