



F-104°

SOLVENT DEGREASER



FEATURES

- Heavy-duty solvent/degreaser
- 104°F (40°C) flash point
- Controlled evaporation
- Safe to use on most surfaces
- Non-conductive
- No rinsing
- No residue
- Inverta Spray Valve

Airbus ABR 9-0140 Type I, Boeing D6-17487
Rev. H, Hamilton Standard O&R Manual,
Learjet LES1239

PACKAGES

Net Content	Part No.
15 wt.oz. /425 g /538 ml aerosol	04920
5 gal. (18.93 liters)	04905
55 gal. (208 liters)	04955

APPLICATIONS

- Air Compressors
- Aircraft Structures
- Bonding Prep
- Cables
- Chains
- Cowlings
- Cranes
- Electric Motors
- Forklifts
- Gasoline Engines
- Gears
- Landing Gear
- Machine Tool Clean Up
- Power Tools
- Terminals

PROPERTIES

Auto Ignition Temperature:

>442°F (228°C)

Boiling Point:

~ 315 °F (157°C)

Color:

Colorless / water-white

Evaporation Rate:

0.15 (BuAc=1)

Flammable limits (estimated):

LEL: 0.7%

UEL: 6%

Flash Point (TCC):

104°F (40°C)

Odor:

Mild Orange

Partition Coefficient (octanol/water):

<1

Rule 1171 PPc:

<5 mmHg at 68°F (20°C)

Specific Gravity (Water=1):

0.77-0.79 @ 77°F (25 °C)

Total Composite Vapor Pressure:

~2 mmHg at 68°F (20°C)

Vapor Density (air=1):

4.8-5.3

Viscosity:

<3 cSt @ 77°F (25 °C)

VOC Content:

Aerosol: 97.2%, 755 g/L, 6.3 lb/gal.

Bulk: 100%, 777 g/L, 6.5 lb/gal.

Volatiles:

100%



MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE :WWW.LPSLABS.COM

LPS Laboratories • An Illinois Tool Works Company

P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: www.lpslabs.com

©2010 LPS Laboratories • LPS® is a registered trademark of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2137 • Rev. 5/2010