



# RTV CLEAR SILICONE

## ADHESIVE AND SEALANT



### FEATURES

- Waterproofs, seals, bonds, insulates and protects
- Cures at room temperature
- Forms a watertight seal that is ideal for ductwork and electrical applications
- Can be used on metal, plastic, wood and glass
- Can be applied to horizontal or vertical surfaces
- Ideal for gasket making
- Not affected by vibration
- Nonflammable and nontoxic

### APPLICATIONS

- Bonding plastic materials to metal
- Compressors
- Ductwork
- Electrical equipment
- Gasket making
- Gear Boxes
- HVAC
- Industrial
- Screwless brackets

### PROPERTIES

#### Uncured Material

Chemical Type: Acetoxy silicone rubber

Appearance: Clear, non-sag paste

Odor: vinegar

Specific Gravity: 1.00 - 1.04

Extrusion rate @ 25°C, (grams/min):  
>220

Flash Point: >200°F, (93°C)

**Cured Material: After 7 days at 77°F (25°C), 50% relative humidity**

Hardness (Shore A): >20 (typical)

Elongation: Material will stretch 3.5 times its original length before breaking.

Continuous Temperature Resistance:  
-75°F to 400°F (-59°C to 204°C)

Intermittent Temperature Resistance:  
-75°F to 500°F (-59°C to 260°C)



MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE : [WWW.LPSLABS.COM](http://WWW.LPSLABS.COM)

### PACKAGE

Net Fill  
7.25 oz. (205 grams) pressurized tube

Part No.  
03712

LPS Laboratories • An Illinois Tool Works Company

P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: [www.lpslabs.com](http://www.lpslabs.com)

©2007 LPS Laboratories • LPS® is a registered trademark of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2217• Rev.5/2007