



DATA / SPECIFICATION SHEET

MP 4158

PURE PTFE WITH ARAMID FIBER AT CORNERS

DESCRIPTION

Masterpac MP 4158 is a pure PTFE fiber yarn heavily impregnated with aramid fiber at each corners. This latter improves both the adjustability and the lubrication while reducing shaft wear. MP 4158 is being recommended for many applications including rotary and reciprocating pumps, mixers, blenders, agitators, valves amongst others.

USE

Min. Temperature	: -250° C
Max. Temperature	: +260° C
Max. Pressure	: 500 psi (Rotary)
Max. Rotary Speed	: 2500 fpm (12 m/s)
pH Range	: 2-12
Construction	: Inter-Braided

AVAILABILITY

Standard Size	: 3mm x 3mm to 25mm x 25mm
Standard Weight	: 5.5 lbs (2.5 kgs) 11.0 lbs (5.0 kgs)

As the company's products are used for a multiplicity of purposes and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of the company

MASTERPAC-ASIA COMPANY LIMITED

135/18 Amornphan 205 Tower 2 Bldg., 8th Flr., Soi Nathong Ratchadaphisek Rd., Bangkok 10400 THAILAND
Tel +66-0-2689-5393 to 6 Fax +66-0-2689-5397 to 8 www.mpac-asia.com E-Mail : enquiry@mpac-asia.com