



DATA / SPECIFICATION SHEET

MP 1890F

RAMIE FILAMENT WITH PTFE DISPERSION

DESCRIPTION

Masterpac MP 1890F is a long ramie fiber braided square and thoroughly impregnated with mineral grease plus PTFE to make the packing pliable and resilient. MP 1890F is typically used in reciprocating pumps, valves, and plungers in order to seal hot and cold water. It is ideally suitable for marine use.

USE

Min. Temperature	: -100°C
Max. Temperature	: +260°C
Max. Pressure	: 500 psi (Rotary)
Max. Rotary Speed	: 2000 fpm (10 m/s)
pH Range	: 4-12
Construction	: Inter-Braided

AVAILABILITY

Standard Size	: 3mm x 3mm to 25mm x 25mm
Standard Weight	: 5.5 lbs (2.5 kgs)
	11.0 lbs (5.0 kgs)

As the company's products are used for a multiplicity of purposes and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of the company

MASTERPAC-ASIA COMPANY LIMITED

135/18 Amornphan 205 Tower 2 Bldg., 8th Flr., Soi Nathong Ratchadaphisek Rd., Bangkok 10400 THAILAND
 Tel +66-0-2689-5393 to 6 Fax +66-0-2689-5397 to 8 www.mpac-asia.com E-Mail : enquiry@mpac-asia.com