



DATA / SPECIFICATION SHEET

MP 4188

ARAMID FILAMENT WITH PTFE DISPERSION

DESCRIPTION

This unique packing has the strength of Kevlar aramid fiber yarn heavily impregnated with PTFE and saturated with inert lubricant. Masterpac MP 4188 is recommended for extreme applications on reciprocating pumps that handle highly abrasive slurries or aggressive chemical solutions in the mineral, pulp and paper, waste water and chemical processing industries.

USE

Min. Temperature	: -250° C
Max. Temperature	: +260° C
Max. Pressure	: 500 psi (Rotary)
Max. Rotary Speed	: 3000 fpm (15 m/s)
pH Range	: 2-12
Construction	: Inter-Braided

AVAILABILITY

Standard Size	: 3mm x 3mm to 25mm x 25mm
Standard Weight	: 5.5 lbs (2.5 kgs)
	11.0 lbs (5.0 kgs)

As the company's products are used for a multiplicity of purposes and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of the company

MASTERPAC-ASIA COMPANY LIMITED

135/18 Amornphan 205 Tower 2 Bldg., 8th Flr., Soi Nathong Ratchadaphisek Rd., Bangkok 10400 THAILAND
 Tel +66-0-2689-5393 to 6 Fax +66-0-2689-5397 to 8 www.mpac-asia.com E-Mail : enquiry@mpac-asia.com