



SYNTHETIC FILAMENT WITH PTFE SUSPENSOID

DATA / SPECIFICATION SHEET

MP 1900

DESCRIPTION

Masterpac MP 1900 made from polyacrylonitrile filament lattice braided and fully blocked with PTFE. This packing has high strength and impact resistance. It is an ideally replacement for asbestos and typically used in valves and pumps, centrifugal, and reciprocating.

USE

Min. Temperature : -110°C
 Max. Temperature : +260°C
 Max. Pressure : 300 psi (Rotary)
 Max. Rotary Speed : 1500 fpm (8 m/s)
 pH Range : 2-12
 Construction : Lattice Braided

AVAILABILITY

Standard Size : 3mm x 3mm to 25mm x 25mm
 Standard Weight : 5.5 lbs (2.5 kgs)
 11.0 lbs (5.0 kgs)

As the company's products are used for a multiplicity of purposes and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of the company

MASTERPAC-ASIA COMPANY LIMITED

135/18 Amornphan 205 Tower 2 Bldg., 8th Flr., Soi Nathong Ratchadaphisek Rd., Bangkok 10400 THAILAND
 Tel +66-0-2689-5393 to 6 Fax +66-0-2689-5397 to 8 www.mpac-asia.com E-Mail : enquiry@mpac-asia.com