

Flexitallic®

n novus™
a Flexitallic brand

Data / Specification Sheet • Novus 20

Novus 20 is a good quality compressed sheet material based on aramid fibre with a nitrile rubber binder system.



Service

Novus 20 is a general purpose material suitable for use in a wide range of applications, including hot and cold water, steam, oils, fuels, gases and a wide range of general chemicals.

Approvals / Compliance

DIN-DVGW (Gas Industry)
NG-5123AM 0226

WRAS Potable Water:
Registration No. 0402502

Complies with BS Specification 7531
Grade Y

Availability

Thickness range:
0.25mm to 6.0mm

Standard sheet sizes:

2.0m x 2.0m
2.0m x 1.5m
2.0m x 1.0m
1.5m x 1.5m
1.5m x 1.0m

Standard roll sizes:

Up to a maximum size of 6.0m x 2.0m


Available with fine mesh mild steel reinforcement: Novus 20 Metallic, or gauze mild steel wire reinforcement: Novus 20 GWI.

It can also be supplied with anti-stick and graphite coating.

Physical properties

Thickness		1.5mm
Density		1.9g/cc
Tensile Strength	ASTM F152	14MPa
Compression	ASTM F36	8%
Recovery	ASTM F36	55% min
Residual Stress	BS 7531 (300°C) DIN 52913	23MPa 29MPa
Gas Leakage	BS 7531	<1.0cc/min
ASTM Oil 1	Thickness increase	2.0%
IRM 903 Oil	Thickness increase	5.0%
ASTM Fuel B	Thickness increase	2.5%

Novus 20 Pressure/Temperature Limits



- ① Suitable subject to chemical compatibility.
- ② Suitable in some cases but check your application requirements with Flexitallic.
- ③ Contact the Technical Team for applications with higher temperatures and pressures. Applicable to 1.5mm and below.

The operating temperature of non-asbestos sheet material is related to the thickness of materials selected. Thinner materials give better temperature and pressure properties.

As the company's products are used for a multiplicity of purposes and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only, and without liability on the part of the company.