



T-91

GOING
GREEN

Non-Solvent Degreaser

An environmentally safe, green degreaser that outperforms most solvents.



FEATURES

- Contains no solvents
- Premium performance cleaning ability
- Zero VOCs
VOC's per CARB/OTC/LADCO: 0 g/L
VOC content per SCAQMD: 0 g/L
- "Green": Recognized by U.S. EPA's (Environmental Protection Agency) "Design for the Environment" Requirements
- Biodegradable
- Listed in the USDA BioPreferredSM Catalog
- Non-flammable, non-toxic, low odor
- Proprietary formula
- Efficient: requires less product than traditional solvents to get the job done
- Ideal for traditional solvent cleaning, basin style part washers and dip tanks
- Moderate foam for effective mechanical cleaning
- Acceptable for use in Canadian Food Processing Establishments.



Recognized for
Safer Chemistry
www.epa.gov/dfe



Nonfood Compounds
Program Listed
Category Code:
A1 Registration
141975 (Bulk)



APPLICATIONS

- | | | |
|-----------------|-----------------|----------------|
| • Bilges | • Engines | • Grease Traps |
| • Compressors | • Floors | • Machinery |
| • Concrete | • Forklifts | • Marine |
| • Dip Tanks | • Basin Style | • Tanks |
| • Drill Presses | • Parts Washers | • Tools |

PACKAGES

Net Contents

- NEW** - 28 fl .oz. (828 mL) trigger
- 1 gal. (3.78 liters) container
- 5 gal. (18.93 liters) pail
- 55 gal. (208 liters) drum

Part No.

- 06328**
- 06301
- 06305
- 06355



T-91

GOING
GREEN

Non-Solvent Degreaser

An environmentally safe, green degreaser that outperforms most solvents.

ELIMINATES OR REDUCES THE NEED FOR THE FOLLOWING CHEMICALS

- Acetone
- Acids
- Alcohol
- Butyl
- Caustic
- Flammable products
- High VOC cleaners
- Kerosene
- MEK (Methyl Ethyl Ketone)
- Mineral Spirits
- Phosphates
- Stoddard solvents
- Toluene

APPLICATION DILUTION CHART

AS A DIRECT SOLVENT DEGREASER REPLACEMENT:

Use T-91 undiluted (straight) as a direct solvent replacement for all heavy duty degreasing applications.

DILUTION RATIO PRODUCT (AS A NEUTRAL pH CLEANER) WATER	APPLICATIONS: (SUGGESTED DILUTION RANGES FOR CLEANING SURFACES NOT DAMAGED BY WATER ALONE)
1:10 – 1:75	Floors: Light to Heavy Duty Cleaning/Degreasing
Undiluted to 1 : 10	Metals: Heavy Duty Cleaning/Degreasing
1:20 – 1:80	Plastics, rubbers & painted surfaces
1:50 – 1:100	Glass
1:10 – 1:80	Pressure Washing: Light to Heavy-Duty Cleaning/Degreasing
1:10 – 1:25	Soak Tanks [Do Not Exceed 140°F (60°C)]

NOTE:

- (1) A fresh water rinse is recommended after using stronger dilutions.
- (2) Limit exposure time and temperature when cleaning sensitive, non ferrous metals such as aluminum and copper to avoid potential darkening of the metal surface.

PROPERTIES

Appearance:

Colorless, Clear Liquid

Specific Gravity (Water=1):

1.035

Flash Point:

None

pH:

7.3 to 7.7

Boiling Point:

> 212°F (> 100°C)

V.O.C. Content:

0 g/L per EPA SCAQMD
Rule 102/CARB/OTC/
LADCO

Vapor Pressure:

18 mmHg

Viscosity:

~5 cps

Volatiles:

70% – 90%

MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEBSITE: WWW.LPSLABS.COM

LPS Laboratories • An Illinois Tool Works Company

P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Website: www.lpslabs.com

©2010 LPS Laboratories • LPS® is a registered trademark of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2233 • Rev. 10/2010