



PLASTIC SAFE ELECTRICAL CLEANER

PLASTIC SAFE Electrical Cleaner is the non-flammable, fast-evaporating cleaner that's safe on plastics and does not contain HCFCs.



FEATURES

- Safe on plastics
- Fast evaporating, leaves no residue
- Non-flammable
- Does not contain HCFCs
- Formulated for contact cleaning
- VOC compliant in all 50 states
- NSF® Registered K2 # 129002



SPECIFICATIONS AND APPROVALS

- Cessna Approval #244689
- General Motors Co.
- Inland Steel
- Kimberly-Clark
- Minntac - US Steel
- NSF International
- Tyson

PACKAGE SIZES

Net Contents

18 wt.oz. / 510 g/ 412 ml aerosol

Part No.

04620

APPLICATIONS

- Connectors
- Electrical Contacts
- Magnetic Heads
- Office Equipment
- Printed Circuit Boards
- Printers
- Relays
- Solenoids
- Switches
- Telecommunications Equipment



PLASTIC SAFE ELECTRICAL CLEANER

PROPERTIES

Appearance/physical state	Liquid	Partition coefficient (n-octanol/water)	<1
Color	Colorless	Viscosity	<3 cSt @ 25 °C
Odor	Mild, ether-like	Heat of combustion	<20 kJ/g
Boiling point	383 °F (195 °C)	Percent volatile	100%
Flash point	N/A	Specific gravity	1.34 @ 25 °C
Evaporation rate	>1 (Ethyl Ether = 1)	VOC (weight%)	30.6% per California Consumer Product Regulations 11.6% per U.S. State and Federal Consumer Product Regulations
Solubility(ies)	<5% w/w	Propellant Type (aerosol)	Carbon dioxide

DIRECTIONS

DO NOT use on energized electrical equipment or equipment in operation and allow surface to dry before restart. Hold can 6-8 inches away and spray directly on surface to clean. Test on a small inconspicuous area or similar expendable component prior to use to assure material compatibility. Lubricate and protect the clean surface with your choice of LPS® lubricants and corrosion inhibitors.

HANDLING

DO NOT spray into or around ignition sources. After handling, always wash hands thoroughly with soap and water. Use only with adequate ventilation. Avoid breathing vapors or spray mists. Avoid contact with eyes, skin, and clothing. Ground and bond containers before transferring materials.

STORAGE

Keep container in a cool, dry, well-ventilated area. Avoid all sources of ignition (spark or flame). Store below 120 °F.

MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE : WWW.LPSLABS.COM

LPS® Laboratories • An Illinois Tool Works Company
4647 Hugh Howell Road • Tucker, GA 30084 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899
Internet Web Site: www.lpslabs.com

©2014 LPS® Laboratories • LPS® is a registered trademark of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #TDS_04320 • Rev. 7/2014