



DATA / SPECIFICATION SHEET

MP 8005



PURE FLEXIBLE GRAPHITE

DESCRIPTION

Masterpac MP 8005 is a pure flexible graphite fiber yarn with corrosion inhibitors. The benefits are a high temperature and speed capacity. It is highly suitable for steam valves, boiler feed pumps, condensate pumps, chemical and petrochemical applications, expansion joints and high temperature groove packing.

AVAILABILITY

Standard Size : 3mm x 3mm to 25mm x 25mm
 Standard Weight : 5.5 lbs (2.5 kgs)
 11.0 lbs (5.0 kgs)

USE

Min. Temperature : -240° C
 Max. Temperature : +650° C (steam)
 +455° C (atmosphere)
 Max. Pressure : 3000 psi (Valve)
 Max. Rotary Speed : 4000 fpm (20 m/s)
 pH Range : 0-14
 Construction : Inter-Braided

As the company's products are used for a multiplicity of purposes and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of the company

MASTERPAC-ASIA COMPANY LIMITED

135/18 Amornphan 205 Tower 2 Bldg., 8th Flr., Soi Nathong Ratchadaphisek Rd., Bangkok 10400 THAILAND
 Tel +66-0-2689-5393 to 6 Fax +66-0-2689-5397 to 8 www.mpac-asia.com E-Mail : enquiry@mpac-asia.com