



DATA / SPECIFICATION SHEET

MP 4130L



PURE PTFE FILAMENT WITH FOOD GRADE LUBRICANT

DESCRIPTION

According to the nature of PTFE, care must be taken when using in rotary service to avoid burning and glazing of packing during start-up period. Masterpac MP 4130L is manufactured with a pure PTFE filament and silicone oil lubricant which incorporated with the packing during manufacture to provide compatibility with chemicals, food & potable water. It is excellent for food and drinks industry and highly recommended for petrochemical, pumps and valve in strong acid and alkali services.

AVAILABILITY

Standard Size : 3mm x 3mm to 25mm x 25mm
Standard Weight : 5.5 lbs (2.5 kgs)
11.0 lbs (5.0 kgs)

USE

Min. Temperature : -268° C
Max. Temperature : +260° C
Max. Pressure : 300 psi (Rotary)
Max. Rotary Speed : 1500 fpm (8 m/s)
pH Range : 0-14
Construction : Inter-Braided

As the company's products are used for a multiplicity of purposes and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of the company

MASTERPAC-ASIA COMPANY LIMITED

135/18 Amornphan 205 Tower 2 Bldg., 8th Flr., Soi Nathong Ratchadaphisek Rd., Bangkok 10400 THAILAND
Tel +66-0-2689-5393 to 6 Fax +66-0-2689-5397 to 8 www.mpac-asia.com E-Mail : enquiry@mpac-asia.com