



DATA / SPECIFICATION SHEET

MP 4140GFO



GFO WITH LUBRICANT

DESCRIPTION

Masterpac MP 4140 is a pure PTFE fiber yarn heavily impregnated with ultra pure graphite powder and lubricated with an inert lubricant to provide both lubrication and heat dispersion benefits. MP 4140 also known as GFO in general industry and being recommended for many applications including rotary and reciprocating pumps, mixers, blenders, agitators, valves amongst others.

USE

| | |
|-------------------|---------------------|
| Min. Temperature | : -130°C |
| Max. Temperature | : +288°C |
| Max. Pressure | : 300 psi (Rotary) |
| Max. Rotary Speed | : 4400 fpm (22 m/s) |
| pH Range | : 0-14 |
| Construction | : Inter-Braided |

AVAILABILITY

| | |
|-----------------|----------------------------|
| Standard Size | : 3mm x 3mm to 25mm x 25mm |
| Standard Weight | : 5.5 lbs (2.5 kgs) |
| | 11.0 lbs (5.0 kgs) |

As the company's products are used for a multiplicity of purposes and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of the company

MASTERPAC-ASIA COMPANY LIMITED

135/18 Amornphan 205 Tower 2 Bldg., 8th Flr., Soi Nathong Ratchadaphisek Rd., Bangkok 10400 THAILAND
 Tel +66-0-2689-5393 to 6 Fax +66-0-2689-5397 to 8 www.mpac-asia.com E-Mail : enquiry@mpac-asia.com